

Specifications

EC750SA/EC1000SA

The following conditions are provided unless otherwise noted.

- Signal source: INT (internal signal source) • Output waveform: sine wave
- Load: resistance load for power factor 1 • Output terminal: Rear panel output terminal block

■AC/DC Mode, Signal Source

AC/DC Mode	AC, AC+DC
Signal Source	INT(Internal), EXT(External), ADD(Internal and external), SYNC(External synchronization)

■Power Output

AC Output	
Output Power	EC750SA: 750 VA EC1000SA: 1000 VA (When the input is from AC180 V to 250 V, hereinafter referred to as "AC 200V input system") When the input is from AC 100 V to 180V (hereinafter referred to as "AC 100 V input system"), output power is limited to 750 VA.
Rated Output Voltage	100 Vrms/200 Vrms
Output Range	100 V range/200 V range
Voltage Setting Range ^{*1 *2}	0.0 to 155.0 Vrms/0.0 to 310.0 Vrms (Resolution 0.1 Vrms)
Voltage Accuracy ^{*3}	± (0.5% of set + 0.6 Vrms/1.2 Vrms)
Max. Current ^{*4 *5 *6 *7}	10 Arms/5 Arms
Max. Peak Current ^{*4 *8 *9 *10}	EC750SA: 30 Apk/15 Apk EC1000SA: 40 Apk/20 Apk
Frequency Setting Range ^{*11}	1.0 Hz to 550.0 Hz (Resolution 0.1 Hz)
Frequency Accuracy	±0.01% of set (1.0 Hz to 550.0 Hz, 23°C±5°C)
Output Waveform ^{*11}	Sine wave, square wave, arbitrary wave (16 types)
Output On Phase ^{*11}	0.0 deg. to 359.9 deg. variable (resolution 0.1 deg.)
DC Offset	±50 mV/±100 mV (typ., fine adjustment available, AC mode)
Small Amplitude Frequency Response ^{*12}	AC mode: 1% (40 Hz to 550 Hz) AC+DC mode: 1% (40 Hz to 550 Hz)
DC Output	
Output Power	EC750SA: 750 W EC1000SA: 1000 W (AC 200 V input system) (For the AC 100 V input, output power is limited to 750 W)
Rated Output Voltage	100 V/200 V
Voltage Setting Range ^{*1 *2}	-220.0 V to +220.0 V/-440.0 V to +440.0 V (Resolution 0.1 V)
Voltage Accuracy ^{*13}	± ([0.5% of set]+0.6 V/1.2 V)
Max. Current ^{*4 *5}	10 A/5 A
Max. Peak Current ^{*4 *8}	EC750SA: 30 Apk/15 Apk EC1000SA: 40 Apk/20 Apk
Output Voltage Stability	
Fluctuation with output current	45 Hz to 65 Hz: Within ±0.15%, DC and 40 Hz to 550 Hz: Within ±0.5% EC750SA: In the case that the output current is changed and the output power is changed from 0% to 100% of the maximum output power, at the output terminal) EC1000SA: In the case that the output current is changed from 0% to 100% of the maximum current, at the output terminal, rated output voltage)
Fluctuation with input voltage	Within 0.2% (power input voltage: 100 V/120 V/230 V, no load, rated output)
Output Voltage Distortion Factor	0.5% or lower (50 Hz/60 Hz, 50% or higher of rated output voltage)
Output terminal ^{*14}	Terminal with M4 screws (rear panel), AC outlet (universal type, front panel)

^{*1} Signal source: INT, SYNC or ADD, no load ^{*2} The AC settings (peak value) + DC setting that can be set are within the voltage setting limit range ^{*3} AC Mode, 50 Hz/60 Hz, 23°C±5°C, Sine wave, no load, 10 V to 155 V/20 V to 310 V
^{*4} The limit on max. output power may cause a reduction in max. output current and max. peak current (EC1000SA for power input AC100 V) ^{*5} For At or above the rated output voltage, the limit on max. output power reduces max. output current. (EC1000SA only). ^{*6} In the case of 40 Hz or lower, or 400 Hz or lower, max. output current may decrease. ^{*7} The RMS current of AC + DC is max. output current ^{*8} For At or above the rated output voltage, the limit on max. output power reduces max. output peak current. ^{*9} For a capacitor input type rectifier circuit (crest factor = 4)
^{*10} In the case of 45 Hz or lower, or 65 Hz or higher, max. output peak current may decrease. ^{*11} Signal source: INT, SYNC or ADD, no load ^{*12} Signal source: INT and SYNC, 100 V range, output voltage: 20 Vrms, 50 Hz rating
^{*13} Signal source: AC+DC, AC0 V setting, 23°C±5°C, no load, -220 V to -10 V, +10 V to +220 V/-440 V to -20 V, +20 V to +440 V ^{*14} Use AC outlet for AC (AC0 V to 250 V). When DC is included, use screw terminal on the rear panel.

■Power Input

Voltage	100 V to 230 V±10% (Max. voltage 250 V), Overvoltage Category II
Frequency	50 Hz/60 Hz ±2 Hz (single phase)
Power Factor (typ.) ^{*15}	0.95 or higher (at AC100 V input), 0.90 or higher (at AC200 V input)
Max. Power Consumption	EC750SA: 1.2 kVA or lower EC1000SA: 1.4 kVA or lower

^{*15} The rated output voltage, the resistance load at the maximum current

■Measurement Function

Voltage	
RMS Value (AC+DC: rms)	Full scale: 250.0 V/500.0 V, Resolution: 0.1 V
Average (AC+DC: avg)	Full scale: ±250.0 V/±500.0 V, Resolution: 0.1 V
Peak Value (Max/Min Individual: pk)	Full scale: ±250 V/±500 V, Resolution: 1 V
Current	
RMS Value (AC+DC: rms)	Full scale: 15.00 A, Resolution: 0.01 A
Average (AC+DC: avg)	Full scale: ±15.00 A, Resolution: 0.01 A
Peak Value (Max/Min Individual: pk)	Full scale: ±45.0 A, Resolution: 0.1 A Hold the maximum values of max and min
Power	
Effective (W)	Full scale: 1200 W, Resolution: 1 W
Apparent (VA)	Full scale: 1400 VA, Resolution: 1 VA
Reactive (var)	Full scale: 1400 var, Resolution: 1 var
Load Power Factor	Measurement range: 0.00 to 1.00, resolution: 0.01
Load Crest Factor ^{*16}	Measurement range: 1.00 to 50.00, resolution: 0.01
External Synchronization Frequency (SYNC mode only)	Measurement range: 38.0 to 525.0 Hz, resolution: 0.1 Hz
Output Harmonic Current ^{*17}	Measurement range: Up to 40th order, Full scale: 15 Arms and 500%

^{*16} Calculated as output voltage RMS value × output current RMS value ^{*17} This measurement doesn't comply with the IEC standards.

- [set] indicates a setting value.
 - A value without the accuracy is the nominal value or representative value (shown as typ.)
 - When two values are indicated with a slash, this means that specifications vary depending on the output range. The value before the slash is for 100 V specifications, and the value after the slash is for 200 V specifications.

■Current Limiter

Peak	
Positive current	EC750SA: +10.0 A to +31.5 A/+5.0 A to +15.8 A (Resolution: 0.1 A) EC1000SA: +10.0 A to +42.0 A/+5.0 A to +21.0 A (Resolution: 0.1 A)
Negative current	EC750SA: -31.5 A to -10.0 A/-15.8 A to -5.0 A (Resolution: 0.1 A) EC1000SA: -42.0 A to -10.0 A/-21.0 A to -5.0 A (Resolution: 0.1 A)
Limiter operation	When limiter is operating, output voltage is clipped.
RMS	
Setting range	1.0 A to 10.5 A (initial value: 10.5 A)/1.0 A to 5.3 A (initial value: 5.3 A), (Resolution 0.1 A)
Limiter operation	When limiter is operating, suppresses output voltage.

■Sequence Function

Sequence function works with AC-INT, AC+DC-INT.	
Number of Memories	One sequence per AC/AC+DC mode at both 100 V and 200 V range.
Number of Steps	255 max. (for each sequence)
Setting Range of Step Time	0.1 ms to 999.9999 s (Resolution: 0.1 ms)
Operation within Step	Constant, keep, linear sweep
Parameters	DC voltage, AC phase voltage, frequency, waveform, synchronous step output (2 bit)
Jump count	1 to 999 or infinite
Sequence Control	Start, stop, hold, branch

■Control Software

Functions	
Remote Control	Parameter setting, store/recall, status monitoring
Logging	Reads and saves measured values.
Arbitrary Waveform	Waveform creation and edit, transfer, display and file operations
Sequence	Sequence data creation, edit, save, transfer, execution control
Operating Requirements	
CPU	300 MHz min. (CPU clock needed for the correspondence OS or faster)
Memory	128 MB min.
Free Hard Disk Space	64 MB min.
OS	Microsoft Windows XP/7 (32 bit), Microsoft Windows 7 (64 bit)
Disk Drive	CD-ROM drive
Interface	USB 1.1 or higher

■Other Functions

Setting range limit function ^{*11}	
Voltage	Positive voltage setting range +0.1 V to +220.0 V/ +0.1 V to +440.0 V (Resolution: 0.1 V)
	Negative voltage setting range -0.1 V to -220.0 V/ -0.1 V to -440.0 V (Resolution: 0.1 V)
Frequency (Lower limit≤Upper limit)	Upper limit setting range 1.0 Hz to 550.0 Hz (Resolution: 0.1 Hz) Lower limit setting range 1.0 Hz to 550.0 Hz (Resolution: 0.1 Hz)
Arbitrary Wave	
Number of memories	16 (nonvolatile)
Waveform length	4096 words
External Signal Input	
External Signal Input (EXT/ADD mode)	Gain setting range: 0.0 to 220.0 times/0.0 to 440.0 times (Resolution: 0.1) Frequency range: DC to 550 Hz (sine wave)
External Sync Input (Sync mode)	Sync signal source: external sync signal (EXT) or power input (LINE) Sync frequency range: 40 Hz to 500 Hz
Memory Function	Store and recall settings, Basic settings: 30
Protections	Protective operation for abnormal output , power unit error, internal control error, and abnormal internal temperature
External Control I/O	Enables control of the system using external signals . Control input, state output
Interface	USB (USBTMC), RS-232
LCD Display	White or blue base color.
Others	Beep, keylock, output setting at power-on, reset function, self test function

■Generals

Withstanding Voltage and Insulation Resistance	AC1500 V, Insulation Resistance : 30 MΩ or higher (DC 500 V)
Operating Temperature/Humidity	0°C to +40°C/5% to 85%RH (absolute humidity 1 to 25 g/m³, no condensation)
Dimensions (mm)	258(W)×176(H)×440(D) (not including protrusions)
Weight	Approx. 9.7 kg
Safety	EN61010-1:2010
EMC	EN61326-1:2006 (Group 1, Class A) EN61000-3-2:2006 + A1:2009 + A2:2009 EN61000-3-3:2008
RoHS	Directive 2011/65/EU
Accessories	Operation manual, control software, power cord set 1 (15 A/125 V), power cord set 2 (10 A/250 V, without plug, EC1000SA only)

The contents of this catalog are current as of July 15, 2015.

- External view and specifications are subject to change without prior notice.
- Please check the latest specifications, prices, and lead time for purchase.
- The company names and product names described here are trademarks or registered trademarks of respective owners.

NF Corporation

● Head Office
6-3-20 Tsunashima Higashi, Kohoku-ku, Yokohama 223-8508, Japan
<http://www.nfcorp.co.jp/english/>

NF Techno Commerce Co., Ltd. International Sales Division
Meiko Building, 3-1-13 Nishi-Ikebukuro, Toshima-ku, Tokyo 171-0021, Japan
Phone : +81-3-5957-1809 Fax : +81-3-5957-1813